LETTER
1908
ROSS ET AL ROAD
GEO. FARQUER
MCCLELLAND ET AL ROAD
SAM JORDAN ROAD

Roberts 12 to 24"

Ruel 6" to 12"

1908

Jordan.

7.00
5.95
1.05

West Bridge Foot Hill
B.M. 0.34
Bot St 7.00
Plate 3.95

121.9
39
496.1
655.0

Walbur Stadley
B.M. 4.05
White-Lick Creek
elm Cor S side
Bot St. 10.97
Bot St. 7.41
Sta. 4.35
Cr Ave. 4.35

A. A. Ross Etal Road

Coqm. at E. end of bridge over White Lick creek, which E. end of said bridge is at the E. end of the Superior free gravel road, and running thence S. 87° W. on the Center line of said Bridge 121 9/10 ft to the W. end of said bridge; thence S. 87° W 39 feet thence N 11° W. 494 1/10 feet thence N. 11½° E. 45 feet thence N. 22° E 100 feet thence N. 78 feet to the N line of Sec 4 Tp 15. N. R 1 E. thence running W. on the Sec line between Sec 4 Tp 15 N R 1 E and Sec

23 Tp 16 N. R 1 E to a
Station at the S. W. cor
of said Sec 23; Thence
deflecting to the left
and running a distance
of feet to the N. E.
Cor. of Sec. 5; Thence
running W. on the
line between Sec 5
Tp 15 N. R 1 E and Sec
32 Tp. 16 N. R. 1 E. a
distance of feet
to the line between
Washington and Center
Tps, N Eudnicks Ca Sur

Total distance

Location of E. Abutment of
Hollingsworth Bridge



STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE
B.M	2.15	100			97.85	97.85
0						
1						97.85 X
1+60 21/10				6.30	93.70	95.80 X
2				10.70	89.30	93.92
3				11.20	88.80	090.80 X
4				7.30	92.70	91.15
5				8.50	91.50	91.50 X
6				9.25	90.75	091.98
⊙	6.30	97.05	9.25			
6+55'				3.90	93.15	92.20
7				2.60	94.45	92.46
8				4.05	93.00	92.93
8+78'				4.05	93.00	93.30
9				3.85	93.20	93.40 X
10				3.45	93.60	94.55
11				1.00	96.05	95.70
12				1.15	95.90	96.85
⊙	7.90	103.80	1.15			

Conc. Bridge at Wend.
1+60 2/10 to S.E. 18' from a Fence Post
" NE 23' " " " "

92.70
91.15
1.05

106.20
9.25
97.05
7.90
104.95
1.15
103.80

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE	
		103.80					
13				2.55	101.25	98.00	
14				.90	102.90	99.15	
15				1.50	102.30	100.30 X Sta. 15 = 2 ft Cut	
15+54	0.50	102.80	1.50	6.95	95.85	99.90 S. end Boiler Sewer 5 7/10 Dia X 16 7/10 Long	
16		6.95		7.30	95.50	99.55 Boiler is on a Skew	
17		95.86		7.45	95.35	98.80 Concrete heads to be added to make	
18				6.50	96.30	98.05 each end parallel with center line	
19				5.50	97.30	97.30 X of road and 10 ft therefrom	
20				3.15	99.65	98.02	
⊙	2.95	102.60	3.15				
21				3.90	98.70	98.74	
22				4.30	98.30	99.46	
23				3.85	98.75	100.18	
24				.70	101.90	100.90 X	
⊙	5.45	107.35	.70				
25				6.20	101.15	101.67	
26				5.45	101.90	102.44	
27				4.50	102.85	103.20 X	
28				3.00	104.35	104.50	

6.95
5.75
12.70

7' X 3.5'
4' Skew

102.80
12.70
90.10

99.90
90.10
9.80
2.25
7.55

1.25
.00
2.25

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE	
29		107.35		2.35	105.00	105.86	
⊙	7.80	112.80	2.35				
30				7.10	105.70	107.10	Invert at this point 105.70
31				4.55	108.25	108.40 X	
32				3.10	109.70	114.49	
33				1.15	111.65	120.58	33+25' Sewer 4'X 2.8'
⊙	11.25	122.90	1.15				
34				6.30	116.60	126.67	
⊙	11.55	134.30	0.15				
35				6.70	127.60	132.76	
⊙	11.60	145.70	0.20				
36				5.90	139.80	138.84	
⊙	12.00	157.60	0.10				
37				7.80	149.80	144.92	37+14
38				0.90	156.70	151.00 X	151.
⊙	8.15	164.85	0.90				
39				4.30	160.55	153.07	
40				6.45	158.40	155.14	

12.38
11.25
8.23

126.67
10.07
136.74

STA.	B.S.	H.I.	T.S.	ROD	ELEV.	GRADE
41		164.85		7.65	157.20	157.20 X
42				7.50	157.35	157.84
⊙	6.90	164.25	7.50			
43				4.50	159.75	158.48
44				4.25	160.00	159.11
45				3.20	161.05	159.74
46				4.15	160.10	160.37
47				3.60	160.65	161.00
⊙	6.30	166.95	3.60			
48				5.15	161.80	161.63
49				4.65	162.30	162.26
50				5.25	161.70	162.89
51				5.25	161.70	163.52
52				2.80	164.15	164.15 X
⊙	4.00	168.15	2.80			
53				4.50	163.65	163.79
54				4.25	163.90	163.43
55				3.90	164.25	163.07

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE	
56		168.15		5.00	163.15	162.71	
B.M.	5.75						
⊙ 56+	2.50	164.90	5.75		162.40		B.M. Stone N.E. cor Sec. 5
57				2.60	162.30	162.35	
58				2.10	162.80	162.00	
59				0.85	164.05	161.65	
60				3.30	161.60	161.30	
61				3.90	161.00	160.95	
62				4.50	160.40	160.60 X	
63				5.40	159.50	160.05	
64				4.40	160.50	159.50	
65				5.20	159.70	158.95 X	
66				5.00	159.90	154.95	
⊙	1.40	161.30	5.00				
67				2.55	158.75	150.95	
68				7.30	154.00	146.95	
⊙	0.70	150.00	12.00				
69				7.00	143.00	142.95	
69+48 1/4						139.70 X	
70				11.05	138.95	139.70	
B.M.	10.75		10.75		139.25	139.70	B.M. S.E. cor Wooden Bridge

5.46 Slate to Water line
8.46 " Bottom of Abut
.54 " Mortar rotten to bot floor
1.71 " " " top floor

Elev. Bed Brook line, on Dam Bridge 143.81

STA	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE	
⊙	3.95	143.20	10.75				70+34 Bridge 7' X 20'
71				4.85	138.35	139.70 X	139.70 " 6.90' High
72				2.55	140.65	140.65	
73				6.80	136.40	141.60	
73+80 ⊙	4.65	137.25	10.60			142.35 X	74-½ = Water Line
74				7.40	129.85	142.35	74 is 19' N. of S. end E. abutment
75				6.75	130.50	142.35	of Hollingsworth Bridge
⊙	11.70	148.20	0.75				
76				8.50	139.70	142.35 X	
⊙	10.20	157.75	0.65				
77				8.70	149.05	147.07	
78				1.85	155.90	151.79	
⊙	5.15	162.70	0.20				
79				4.50	158.20	156.50 X	
80				4.15	158.55	157.23	
81				3.60	159.10	157.97	
82				3.20	159.50	158.71	
83				3.25	159.45	159.45 X	
84				2.75	159.95	159.90	

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE
⊙	5.50	165.45	2.75			
85				4.70	160.75	160.35
86				3.70	161.75	160.80
87				3.35	162.10	161.25
88				3.85	161.60	161.70
89				3.50	161.95	162.15
90				2.85	162.60	162.60 X
⊙	5.65	168.00	3.10			
91				5.25	162.75	163.37
92				5.10	162.90	164.14
93				4.85	163.15	164.91
94				3.45	164.55	165.68
95				1.55	166.45	166.45 X
B.M	0.10				167.90	
⊙	6.60	174.50	0.10			
96				6.30	168.20	167.97
97				3.85	170.65	169.49
98				1.60	172.90	171.00 X
99				1.55	172.95	171.95

Sta. 91 to N. end road to be one grade

163.37
162.75
.62

B.M. Cor Stone Cen. S. S½ 4 32-16-1-E

162.60
137
5.37

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE
100				1.20	178.30	172.90
⊙	5.70	179.00	1.20			
101				5.30	173.70	173.85
102				4.35	174.65	174.80
103				3.20	175.80	175.75
104				2.75	176.25	176.70
105				1.50	177.50	177.65
⊙	7.95	185.45	1.50			
106				6.90	178.55	178.60 X
107				5.60	179.85	180.07
108				3.90	181.55	181.54
109				2.80	182.65	183.01
109+68				2.40	183.05	184.00 X
B.M.	1.15				184.30	

B.M. Cor. Stone just N. of entrance. *

Road Estimate

19616 Cu Yds =

4500.

Grading	# 4500
Stone	3475.
Hauling	3475
Sewer Tile, Handling & Laying	85.
Bridge	750
	# 12285

4

Geo Furguson Et al

Geo Fergus

STA	B.S.	H.I.	F.S.	Rod				
B.M	4.70	104.70						
0			7.30	97.40	98.00	X	0.60	On Tp Walnut Post
1			7.25	97.45	98.84		1.39	
2			5.95	98.75	99.67		.92	
3			4.80	99.90	100.50	X	.60	
4			2.90	101.80	103.14		1.34	
5	13.10	115.60	2.20					
5			10.65	104.95	105.78		.83	
6			7.15	108.45	108.42	.03		
7			4.30	111.30	111.06	.24		
8			1.75	113.85	113.70	X .15		
8+75	2.75	117.60	0.75					
8+75			1.90	115.70	113.17	2.53		
9			3.20	114.40	113.00	X 1.40		
9+50			5.80	111.80	111.05	.75		
10			8.40	109.20	109.10	.10		
11			12.10	105.50	105.20	.30		

3.90
1.75
2.15

No cut at 8
" 8.75 cut 2'

STA	B.S.	H.I	F.S.	ROD			Cut	Fill	
0	0.50	106.30	11.80						
12			1	6.35	99.95	101.30		1.35	
13				9.90	96.40	97.40		1.00	
14				12.80	93.50	93.50	.00	.00	
15				13.15	92.15	93.25		.10	
16				14.50	91.80	93.00		1.20	
⊙+BM	7.85	102.95	11.20		95.10				BM. Nail in N. Wing Concrete Box
17				8.95	94.00	95.00		1.00	
18				4.30	98.65	97.00	1.65		22+78 = 24" Sewer
19				2.65	100.30	99.00	1.30		Old is about 16"
20				3.35	99.60	97.65	1.95		
21				6.65	96.30	96.30	.00	.00	
⊙	2.40	99.25	6.10						
22				4.80	94.45	95.60		1.15	Pro. 25
23				4.70	94.55	94.90		.35	Cut 2½ to 3'
24				3.70	95.55	94.20	1.35		
25				2.75	96.50	93.50	3.00		
26				5.70	93.55	91.20	2.35		
27				10.15	89.10	88.90	.20		

STA	BS	H.I	F.S	Rod			Cut	Fill	
BM	5.50				94.75				
28				13.55	85.70	86.60		.90	
29				15.55	83.70	84.30		.60	
On Bridge				15.55	83.70			1.37 above Centerline Br.	
Bed Stream				16.60	79.15				
On Culvert Wheels crossing	2.35	85.00	20.10		82.65			1.62 above Crown foundation	
30				4.00	81.00	82.00		1.00	
31				4.65	78.35	82.10		3.75	
32				5.20	79.80	82.20		2.40	
33				4.80	80.20	82.30		2.10	
34				4.45	80.55	82.40		1.85	
35				3.35	81.65	82.50		.85	
⊙	10.75	93.10	2.65						
36				5.75	87.35	84.44	2.91		
37				4.80	88.30	86.37	1.98		
38				1.80	91.30	88.30	3.00		
39				4.50	88.60	87.60	1.00		
40				7.20	85.90	86.90		1.00	

12.0' left of ft. down to concrete foun. Wheel mark

B.M. - Iffame Post N. side
Near Fargier
Private road
29+91' Bridge
Old Waterway 5.3'
New " 8'
38 Cut 3'
40+46' Sewer 24"
Old " 14"

					Cut	Fill	
41 ✓			7.40	85.70	✓86.20	.50	46+46' is 9.20'
							Sewer - drop 6 to
⊙	2.45	88.15	7.40				put 46 - 6 to
42 ✓			1.30	86.85	✓85.50 x 1.85		30' conc. box
43 ✓			5.50	82.65	83.25	.60	
44 ✓			8.05	80.10	81.00 x	.90	42 cut 12 to 18"
45 ✓			9.40	78.75	✓80.50	1.75	
46 ✓			9.40	78.75	✓80.00 x	1.25	
47 ✓			8.35	79.80	✓80.93	1.13	
⊙	12.00	91.35	8.80				52+47' is a
48 ✓			9.75	81.60	81.86	.26	✓ 18" Sewer
49 ✓			7.30	84.05	82.78	1.27	drop to 6 2' Out
50 ✓			4.65	86.70	✓83.70 x 8.00		
51 ✓			6.65	84.70	✓83.89	.81	
52 ✓			9.00	82.35	✓84.08	1.73	50 cut 3'
53 ✓			8.90	82.45	✓84.27	1.82	50 to end
53+63			7.40	83.95	84.40 x	.45	road 1 grade
end Section							

Cut = 69399 Cut Yd
Fill = 62315 " "
131714

4915 Cu Yds @ 25¢

Grading = $1228.75
Stone 1639 yds @ 1.10 = 1802.90
Hauling = 819.50
Bridge 46 52/100 yds = 850.00
Sewers = 200
Bracing = 50
4451.15

STA.	Above Stakes	Below B. Stakes
0	2ft 1 1/2 in	
3	1ft 2 5/8 "	
8		1/8 in
9		2ft 6 1/2 in
14	9 1/4 in	
16	2ft 10 5/8 in	
19	3 in	
21	1/2 "	
25		3ft 5 1/2 in
30	2ft 7/8 in	
35	3 1/2 "	
38		2ft 7 1/4 in
42		1ft 11 1/8 in
44	Stake on pivot on W. Side	2ft 7 3/4 in
46	2ft 3 1/2 in	
50		3ft 2 1/8 in
53+63	= fill	

N.E. cor 5 ∨ or W cor 4-15-1-E
Wit Stone (M. M. North) 1 ∠ or
" " for S.E cor 33 E 126 E,

S.E. Cor 33 + S.W. cor 34
16-1-E
Wit. Stone N.



McClelland

Beg. at the Sec. cor. common to R. R. 12 W, the same being free grave road, and line between Sec. 33 & 34 Co. Rud. line.

Total distance 5326 ft

Thal Road

to Sec. 27, 28, 33 & 34 Tp 14 the said of the George Reitz running S. on the Sec. proceeded to the Morgan

STA.	B.S	HI	F.S.	ROD	ELEV.	GRADE
B.M	2.75	102.75				B.M. Cor. Stone Common 27, 28, 33 + 34
0				2.75	100.00	100.50 X
1				3.10	99.65	99.51
2				3.95	98.80	98.53
3				5.20	97.55	97.55 X
4				6.70	96.05	95.98
5				8.35	94.40	94.40 X
⊙	3.80	98.20	8.35			
6				4.80	93.40	94.20
7				4.85	93.35	94.00 X
8				3.25	94.95	94.69
9				3.10	95.10	95.38
10				2.95	95.25	96.07
11				1.60	96.60	96.76
12				0.50	97.70	97.45 X
⊙	2.45	100.15	0.50			
13				1.30	98.85	97.45
14				2.70	97.45	97.45 X
15				3.35	96.80	96.65

6 to 7+53' 6' addition N.

If wall goes more E. it is to be from 7+53' N 165'

6+50. Sewer 6'x2'x20'

STA.	B.S.	H.I.	F.S.	ROD	ELEV.	GRADE	
16		100.15		4.20	95.95	95.85	
17				5.10	95.05	95.05 X	
18				5.70	94.45	94.37	
19				5.90	94.25	94.09	
⊙	2.40	96.65	5.90				
20				3.05	93.60	93.61	
21				3.35	93.30	93.13	21+67'- 12" Sewer 18'
22				4.00	92.65	92.65 X	
23				4.05	92.60	92.27	
24				4.60	92.05	91.89	24+72'- 12' Sewer 18'
25				4.60	92.05	91.52	
26				4.70	91.95	91.95 X	
B.M.	5.70				90.95		B.M. ½ Mile Stone
⊙	1.00	91.95	5.70				
27				1.00	90.95	89.91	
28				1.25	90.70	88.68	
29				3.30	88.65	87.45	
30				5.10	86.85	86.22	
31				6.65	85.30	84.99	

STA.	BS.	HI	FS.	ROD	ELEV.	GRADE	
32		91.95		7.85	84.10	83.76	
33				9.40	82.55	82.53	
⊙	2.90	85.45	9.40				
34				4.05	81.40	81.30 X	
35				4.70	80.75	81.30 X	
B.M.	1.65				83.80		B.M. Top log Post - E side road - N. side ditch
				10.00	75.45		Water Line in ditch at Bridge
				4.15	81.30		Top Old Bridge
36				4.30	81.15	82.53	
37				3.35	82.10	83.76	
38				1.15	84.30	84.99	
⊙	7.55	91.85	1.15				
39				4.60	87.25	86.22	
40				4.40	87.45	87.45 X	
41				3.85	88.00	87.15	
42				2.50	89.35	86.86	
43				4.30	87.55	86.57	
44				6.40	85.45	86.28	

STA.	B.S.	HI	F.S.	ROD	ELEV	GRADE	
⊙	3.90	89.35	6.40				
45				4.60	84.75	85.99	45+27'- 18" Sewer 18'
46				4.65	84.70	85.70 X	
47				3.85	85.50	85.82	
48				3.20	86.15	85.9 X	
49				3.45	85.90	86.05	
50				3.80	85.55	86.16	50+64'- 12" Sewer 18'
⊙	7.45	93.00	3.80				
51				7.85	85.15	86.27	
52				5.70	87.30	86.38	
53				6.70	86.30	86.49	
53+26'				7.40	85.60	86.60 X	
BM.	7.75				85.85		BM Stone at End of road

CONTIUOUS GRADE

FROM STA		TO STA
"	0	" 3
"	3	" 5
"	5	" 7
"	7	" 12
"	12	" 14
"	14	" 17
"	17	" 22
"	22	" 26
"	26	" 34
"	34	" 35
"	35	" 40
"	40	" 46
"	46	" 53+26'

Cu Yds = 13742

Grading	750.00
Gravel	450.
Hauling	1500.
Sewer Sys.	70
Hauling	5.
Bridges	400.
	# 3175.

A. A. ROSS ET. AL

STA	STAKE	CENTER	BM.	
109+68	5.17	4.94	4.57	Nail in Post on S side
106	5.50	5.19	4.90	" " " " " "
99	4.53	4.66	4.00	" " " " " "
95	5.59	5.19	5.10	" " " " " "
90	4.94	4.56	4.00	" " " " " "
83	5.58	4.94 Road Graded	5.61	" " " " " "
79	4.09	5.07	4.01	" " " " " "
~~76~~	~~7.82~~			
73+80	at Bridge			" " " " " "
71	4.61	4.94	6.60	" " " " " "
69+81½				
65	5.40	5.00	4.64	" Ends of curb " "
62	4.50	4.95		
57	4.88	4.98	5.21	" " " " " "

This is as far as was staked out

JORDAN ROAD.

	Stake	Center	Run	
0	4.80	4.21	5.00	Beginning Stone.
5	5.30	5.18	5.04	Nail in post on E Side
8	5.29	5.00	5.30	" " " " " "
13	6.24	5.01	5.49	Notch in W. Face on W. "
14	5.11	4.99	4.99	Nail in Post on E. Side
16	5.83	5.64	4.76	S.E. corner of Yard.
18	2.83	3.46.	5.89	N. End of E Abutment of Culvert
19	8.04	10.84	5.89	" " " " " " " "
+35	8.37	6.81	7.00	N. Rail of R.R. in center of Road.
+45	8.05	7.04	7.00	" " " " " " " " "
20	2.19	4.96	7.00	" " " " " " " "
+40	4.03	4.08	1.35	on Bottom step of Barn on E. Side
21+50	5.80	4.71	5.77	Notch in W. Face on W. Side of Road
24	3.34	4.95	3.46	on Stone on W. Side of Road.
29	5.91	5.41	6.88	Nail in fence Post on E Side
34	4.02	4.16	3.35	on S. Stump on W. Side of Road
35	5.52	6.02		
37	5.55	5.30	6.57	Stone under Jordans Barn near Stake

	Stake	center	B.M.
39	3.80	6.17	2.88
41	3.11	3.97	3.22
43	4.01	4.44	4.18
44+50	6.10	4.34	4.18
46	4.10	6.29	4.80
49+35	2.25	3.15	1.70
54.	This is to End of first		

Nail in large Post on E Side
" " " " W "
Stone at S. gate Post on E "
" " " " " " " "
Nail in Post on W Side
" " " " " "
mile.

McCLELLAND

STA	STAKE	CENTER	BM
3	4.36	4.90	4.41
5	4.38	5.02	4.60
7	4.86	4.02	4.84
12	3.96	4.08	4.03
14	5.00	5.14	5.03
17	4.72	4.90	4.86
22	5.29	4.96	5.97
26	4.87	4.85	4.79
34	3.84	4.00	3.46
35	5.12	4.56	5.27
40	4.76	4.58	5.16
46	4.32	4.41	5.44
53+26	5.90	6.32	6.32

ROAD GRADE STAKES

Nail in Tree on W side of Road
" " Post " E " " "
" " " " E " " "
" " " " " " " "
" " Small Tree " W " " "
" " Post " E " " "
" " " " " " " "
" " Maple Tree " W " " "
" " Post " " " " "
" " S " " " " "
" " " " " E " " "
" " " " " " " "
" corner Stone at end of Road

McCLELLAND ROAD.

STA.	A. STAKES	B. STAKES.
3		0.54 FT
5		0.64 "
7	1.49 FT	
12		0.47 "
14		0.14 "
17		0.18 "
22	0.33 "	
26	0.02 "	
34		0.26 "
35	7.11 "	
40	0.18 "	
46	0.91 "	
63+26	0.58 "	

A.A. ROSS ROAD

72

STA	A. STAKES.	B. STAKES.
109+68'	1.18 FT	
106	0.37 "	
98		2.03 FT
95	0.40 "	
90	0.38 "	
83	0.44 "	
79		2.68 "
76		
73+80'		
71	1.02 "	
69+81½'		
65		0.35 "
62		0.25 "
57	0.05 "	
52		0.12 "
41		0.80
38		4.54
31	0.33	

73

STA	ABOVE STAKES	BELOW STAKES
27	1.03 FT	
24		0.73 FT
19	0.79 "	
15		
9	1.19 "	
5	0.10 "	
3	1.02 "	
1+60.9	1.20 "	

SAMUEL JORDAN ROAD.

STA	A. STAKES	B. STAKES.
5	0.12 FT.	
8	0.89 "	
13	0.53 "	
14	0.37 "	
16	0.19 "	
18		1.23 FT.
19		2.80 "
+30	1.56 "	
+45	1.01 "	
20		1.77 "
+40	0.35 "	
21+50	1.09 "	
24		1.61 "
29	0.90 "	
34		0.54 "
35	0.10 "	
37	0.75 "	

STA	A. STAKES	B. STAKES.
39		2.47 FT.
41		0.86 "
43		0.43 "
44+50	1.86 FT.	
46		2.19 "
49+35		2.90 "
54	0.84 "	
57	0.35 "	
61	0.55 "	
62	1.67 "	
66	0.70 "	
68+50	1.21 "	
71		1.34 "
72	0.04 "	
74	3.51 "	
76	0.18 "	
80	0.19 "	
81	0.49 "	

STA	ABOVE STAKES	BELOW STAKES
84		0.94 FT
85		0.10 "
90	0.29FT	
93		1.40 "
96		1.00 "
97+65	10.12 "	
98	10.48 "	
100		0.85 "
102		3.45 "
103	0.22 "	
105	0.70 "	
107		2.83 "
108		0.70 "
110	0.08	
111	0.17	
113		0.33 "
114	0.03	
116		0.05 "
119		0.75 "

STA	ABOVE STAKES	BELOW STAKES
121	0.20 ft	
124	0.31 "	~~0.66 ft~~
127		0.66 ft
129	2.45 "	
130	1.17	
132		0.47 "
134	0.37	
134+22	0.32	


10'6"
Batter Line
3'0"


11'0"
16"
18"
12"
710"
3'0"
43'6"
3'0"

STA	45	-5	ft	Rod		
BM			98.06	.58		
Apron				7.85	72.63	
⊙	10.70	.55	10.70		100.00	
⊙	6.20	6.65	10.25		104.05	
Bottom of				10	92.83	
B.M.				3.19	107.06	Bolt in post
Top				3.21	107.04	
B.M.				1.46	108.79	Stone

RETAINING WALL AT BRIDGE



FOUNDATION PLAN.

Bottom of wall to be 9'2" below top end of present wall.

CATCH BASIN


11'0"
6"
1'6"
3' 6"
Bottom of wall (outside) 9' [redacted]" from nail in fence.
8'0"
7'0"
12"
12"
12"
5' 6"

HEADER ON SOUTH SIDE OF ROAD



Top of wall to be level with grade stake as set.

DITCH LEVELS

5+9	+S	-S	HI	ROD	ELEV
B.M. ground			104.85	4.85	
				5.75	99.10
0				5.30	99.55
1				5.80	99.05
2				6.45	98.40
⊙	3.25	6.45	101.65		
3				4.30	97.35
4				5.25	96.40
5				5.55	96.10
5+31				5.85	95.80
Arm No 1					
0				5.75	96.20
1.				4.25	97.40
1+66				4.55	97.10
2				4.75	96.90
2+63				5.85	95.80
Arm No 2					
0				4.60	97.05
1				3.80	97.85
+55				4.55	97.10

RUSS Road

A.T. Road

Sta	+S	-S	H	Rod	
~~5+31~~ In			101.65	6.85	94.80
0	4.50	5.05	100.30		
6				4.65	95.65
7				4.10	96.20
8				4.60	95.70
9				5.60	94.70
10.		5		5.95	94.35
0	4.85	5.95	97.20		
11				4.90	94.30
12				5.10	94.10
13				6.10	93.10
14				6.55	92.65
15				6.45	92.75
0	4.10	6.45	96.85		
In pond				6.80	90.05
16				3.65	93.20
17				4.60	92.25
18					

In ditch
Top of Tile to be 2'0" below ground at 5+31

Sta	+s	-s	π	Rod	
18			96.85	5.35	91.50
19				8.10	88.75
In ditch				12.00	84.85

~~Sewer trench~~ Intake at 6+42

Intake 9+86

" 14+61

" 17+84

" 19

$2\frac{3}{4}$

15 | 42
30
12

Reference to Boiler Shell at Wilbur Hadleys on Pass Road

N. Record of Bench Mark on Drain Starts at depth 3½ ft per 100' + then to Sta. 25 with at .40 per 100'

Distance from end drain to Boiler Shell 2117' to N. end.

Could not determine depth ditch shown to be at head-
Took reading on surface near heads + forms sd to be
2.76 above bottom of Nw Walls tile - Then assuming
Found 5.59' Fall to Boiler Shell. from Bot Walls tile
Assuming Bot Ditch at head to be 2.74' below Walls tile, there is then
4.85' to Boiler Shell.

From O to Boiler Shell as per King Drain there is 4.60' fall

Boiler Shell N. to N. Hadleys	1st	Tile Fall	.84'
" " " "	2nd	" "	.81
" " " "	3rd	" "	1.80
" " " "	~~Gulch~~ Kings	"	3.12

From Head Bridge to Boiler Shell S. end found Boiler Shell 1.68' higher than Head Bridge

Jan 30-09

Pass Road

King Drain -
shown to Sta 7 with fall of .15'
fall of .25' to 100' + then to end

Shell 2117' to N. end.
shown to be at head-
heads + forms sd to be
Walls tile - Then assuming
from Bot Walls tile
below Walls tile, there is then

King Drain there is 4.60' fall
Tile Fall .84'
" " .81
" " 1.80
" 3.12

found Boiler Shell 1.68' higher than Head Bridge

Reference to Boiler Shell at Wilbur Hadleys on Pass Road

Levels for Bridge a a - Road Rods

B.M. 3.95

Station rod 5.29

Co. Co old Hooden Bridge

2117
7
1717

.25
.14
100
25
3.50
.05
3.55

.75
7
1.00
3.55
4.60 Fall

4) 42
10½

15) 13.5 (.9

154

St. + π −

107.18

100.00
7.92 99.26
4.42

3.30 107.02 3.46

9.49 97.53

3.51 103.88 6.72

Bot Buck Ck

9.40 9.41
3.12

103.81
9.40
94.41

107.18
9.41
1277

11.06
10.87
.19

107.18

107.18
4.60
102.58

7.18
4.42
2.76
3.50
2.76
.74

107.18
7.92
99.26

107

99.26
4.75
4.60
.25

107.18
7.92
99.26

150 - 94.41
55.59

155

Bot Oden

On Taylor
Oak Bluff

Bot Hadley Tel

107.02
3.51
110.53
6.72
103.81

107.18
3.30
103.88

110.48
3.46
107.02
9.49
97.53

.15
3
1.05

2.5
1.4
100
25
350

355
10.5
4.60

2117
700
1417

97.03
94.41
3.1

7.18
7.92

7.92
4.42
3.50
2.76
.74

7.18
4.42
2.76

Nail at Sta 80 est
Hack in post SE 16.70'
" " " SW 23.28

Crossed x Spikes at Bridge
14' E and 14' West of
Center of bridge at
Sta 76+84
with E Nail
Stake "W" SE 24.15'
" "W" SW 19.50'

Wit to West Nail
Stake W NE 19.30'
Stake W NW 23.30'

From Stake Drain line at
Sta 67

15 / 138 (9
135
3

158 No 2 O 4.60

Bridge .030 100

① 4.30
9.62

O 4.40
.54
6.9 x

97.85
30
98.15
4.30
102.45

10.62 Hadley Pt
11.44 Bot Bldr Shell
1062
.82

9.62
4.30
5.32

30

96.53
95.63
.68

100.30
99.70

97.85
30
95.15
9.62
107.77
4.30
103.47
6.94
98.53

98.15
9.62
107.77
4.30
103.47
6.94
98.53

97.85
30
95.15
9.62
5
107.77
4.30
103.47
6.94
96.53

39

Corrugated Pipe
Price

10"	.55 ¢
12"	65
15"	.75
18	85
24	1.25
30	1.75
36	2.25
42	3.06

100.30
9.62
1092

97.85
30
95.15
9.62
.77

98.15
4.30
102.45
9.62
92.83
6.94
85.89

100.00
92.83
7.17

7.2"
6"
6"
7.2"

	S.	6.90	690
Def.	R.	30° 13'	185
"	T	4° 2'	25
"	R	10° 52'	50
"	"	29° 5'	50
"	"	14° 37'	100
"	T	1° 17'	122
S.			12
		5363	3 11

30 13
4 2
26° 11'
10 52
15 19

29 5
15 19
13° 46
14 37
28 23
1 17
27° 6°

71
52
19

65
19
46

S 6.90 | 10' | 11.59
11.52 | 10 | 11.31
11.31 | 21 | .28
21

690
185
25
50
50
100
122
1222

11.29 Stadia Rule
11.31

5363
1222
4141

60

12x9

7½x2⅔ = 10"



4.80
3.75
1.05

2'+12"

1.90
13
1.77

4.59
15
2295
459
6885
520
1385
320
27700
4155
43206

1.41 Ord
9.62
8.78 Hadley Rd
.84

5.29 9.62
8.92
.84
6.64
4.80
1.84 9.62
7.82
1.80

1.59
25
1.84

56+77 Cor Stone

At 56+76,5 Corner

Sta	Bkwk Sur	Cur	BM
3	3.45	2.47	—