


S²SE⁴13-14-2W WARMOTH EST.

1413



Daisy Warmoth Estate

- 1 S² Mi. Stone 13-14-200
- 2 Center of lot hole dug for Con. W. SE⁴
- 3 SW cor. wood cor. post supposed to be SE cor. Towell prop.
- 4 in E. fence Towell prop. near 1/2 sec. line
- 5 Temp. point SE of con. sec. 13
- 6 Post spike found near con. sec. 13
- 7 Temp. point N. of S² Rd.
- 8 " " in S. part of U. S. 40 in E. part of C. R. 300 W. (not used)
- 9 S² Mile Stone 13
- 10 SE cor. stone Sec. 13
- 11 Temp. point in C. R. 300 W.
- 12 SE cor. wood cor. post in new division line
- 13 NW " " " " " " " "
- 14 " " " " " " " "
- 15 stone " " " "
- 16 pipe " " " "
- 17 stone " " " "
- 18 " " " " "
- 19 W. edge wood cor. post " " " "
- 20 small stone " " " "
- 21 NW edge wood cor. post " " " "
- 22 SE " " " " " " " "
- 23 SE cor. " " " for NE cor. of N. parcel
- 24 " " " " S of NE " " Warmoth Est.
- 25 Temp. point in field
- 26 SW cor. wood cor. post for SE cor. Warmoth Est.
- 27 " " Stroud parcel
- 28 SE " " "
- 29 NE " " "
- 30 NW " " "
- 31 Con. W. SE⁴ (midpoint of 1-41; 1. P. set)
- 32 " of Sec. 13 (final loc.); same as 41

33 E N. face R/W marker 40' NWLY L from E National Rd.

34 " " " " " " " " " " " "

35 " " " " " " " " " " " "

36 " " " " " " " " " " " "

37 Calc. position of Cen. E. SE⁴ 13

38 " " " N U.S. 40 opposite point 33

39 " " " E National Road opposite point 33

40 " " " " " " " at line 1-6.

41 " " " Cen. Sec. 13 using Trotter's 2.25 and 6.56 chain distances

42 " " " E National Rd. at N SE⁴ 13

43 intersection of E SE⁴ with line 24-26 (fence)

44 " " " N " " " " " (fence)

45 final NE cor. Warmoth land

46 " SE " " " "

47 midpoint of line 45-46

48 intersection of N S² SE⁴ with line 22-23

BY _____ DATE _____

SUBJECT

Daisy Warmoth Est.


SHEET NO. 1 OF _____

CHKD. BY _____ DATE _____

Pt. S² SE⁴ 13-14-2W

JOB. NO. _____

File: 1342WA



1	***
1 [0.000	***
1 [0.000	***
2	***
4	***
0.0000	***
495.739	***
7 [495.739	***
7 [0.000	***
1.0130	***
2097.307	***
5 [2592.710	***
5 [37.518	***
2	***
5	***
1 [0.000	***
1 [0.000	***
5-1 [180.4945	***
5-1 [2592.982	***

5-1 2593.008' meas.

5-1 2593.000' wtd. mean

1-7 495.746' } adj.

7-5 2097.317' } adj.

USE

To restore con. Sec. 13 from Trotter's 2.25-ch. & 6.56-ch. meas. that appear first in D.R. 83, p. 53.

PRELIMINARY

PRELIMINARY

1	***
1 [0.000	***
1 [0.000	***
2	***
4	***
0.0000	***
495.746	***
7 [495.746	***
7 [0.000	***
1.0130	***
2097.317	***
5 [2592.727	***
5 [37.518	***
3	***
4	***
352.2917	***
57.220	***
6 [2649.456	***
6 [30.038	***
2	***
5	***
0.000	***
0.000	***
1 [180.4945	***
1 [2592.999	***

6 [2649.456	***
6 [30.038	***
1-6 [0.3858	***
1-6 [2649.626	***

Rotate the above
0°38'58" CCW to
make 1-6 a meridian.

1	**
1 [0.000	**
1 [0.000	***
2	***
4	***
359.2102	***
495.746	***
7 [495.714	***
7 [-5.619	***
0.2232	***
2097.317	***
5 [2592.986	***
5 [8.128	***
3	
5	

1 [0.000	***
1 [0.000	***
5-1 [180.1047	***
5-1 [2592.999	***
2	***
4	***
351.5019	***
57.220	***
6 [2649.627	***
6 [0.0005	***
2	***
5	***
1 [0.000	***
1 [0.000	***
6-1 [180.0000	***
6-1 [2649.627	***

AZIMUTHS

P 6		
2	180.21390	***
1	180.1047	***
R.O.	180.0556	***
3	136.1532	***
4	89.2631	***
6	351.5019	***
R.O.	180.05560	***
33	109.3556	***
34	76.2443	***
35	217.2919	***
36	46.1246	***

25	64.39080	***
R.O.	0.2644	***
17	54.0114	***
16	61.2901	***
15	56.3948	***
1	179.2102	***
5	0.2232	***
11	91.2152	***
26	109.0907	***

7	271.21520	***
8	0.2518	***
9	0.2147	***
10	180.0457	***
R.O.	0.3236	***

$$\text{Let } 1 = \frac{1000.000}{1000.000}$$

1	***
1 [1000.000	***
1 [1000.000	***
2	***
4	***
359.2102	***
495.746	***
7 [1495.714	***
7 [994.381	***
3	***
4	***
91.2152	***
2609.542	***
11 [1433.576	***
11 [3603.183	***
2	***
4	***
0.2232	***
2097.317	***
5 [3592.986	***
5 [1008.128	***
3	***
4	***
180.2139	***
1268.626	***
2 [2324.385	***
2 [1000.139	***
136.1532	***
1780.094	***
3 [2306.919	***
3 [2238.887	***
89.2631	***
1231.187	***
4 [3604.978	***
4 [2239.257	***
109.3556	***
84.320	***
33 [3564.702	***
33 [1087.563	***
76.2443	***
632.346	***
34 [3741.549	***
34 [1622.775	***
217.2919	***
40.350	***
35 [3560.969	***
35 [983.571	***
46.1246	***
18.170	***
36 [3605.559	***
36 [1021.245	***
2	***
4	***
351.5019	***
57.220	***
6 [3649.627	***
6 [1000.000	***
2	***
5	***
1 [1000.000	***
1 [1000.000	***
1 [100.0000	***
6-1 [2649.627	***

FINAL


2

1 ***
 11 [1433.576 ***
 3603.183 ***
 3 ***
 4 ***
 0.2147 ***
 2174.156 ***
 9 [3607.688 ***
 3616.959 ***
 2 ***
 4 ***
 180.0457 ***
 468.645 ***
 10 [964.931 ***
 3602.508 ***
 3 ***
 5 ***
 1 [1000.000 ***
 1000.000 ***
 10-1 [270.4619 ***
 2602.744 ***
 $\frac{\Sigma}{n}$ ***
 2 ***
 5 ***
 9 [3607.688 ***
 3616.959 ***
 0.1848 ***
 10-9 [2642.796 ***
 2 ***
 4 ***
 180.1848 ***
 1321.398 ***
 37 [2286.310 ***
 3609.733 ***

1 ***
 33 [3564.702 ***
 1087.563 ***
 2 ***
 5 ***
 34 [3741.549 ***
 1622.775 ***
 33-34 [71.4255 ***
 563.673 ***

P 4
 1 ***
 33 [3564.702 ***
 1087.563 ***
 33-34 71.4255 ***
 2 ***

35 [3560.969 ***
 983.571 ***
 sta./offset [-99.913 ***
 -29.082 ***
 3605.559 ***
 36 [1021.245 ***
 -50.151 ***
 sta./offset [-59.601 ***



try linear regression best fit line:


	x	y	$\hat{y}$
35	-99.913	-0.918	-0.5046
36	-50.151	-0.399	-0.4617
33	0.000	0.000	-0.4184
34	563.673	0.000	+0.0677

$y = 0.000862x - 0.4184$
 $\phi = 0^\circ 02' 58''$
 $71^\circ 42' 55'' - \phi = 71^\circ 39' 57''$

P 1
 1 ***
 33 [3564.702 ***
 1087.563 ***
 2 ***
 4 ***
 161.4255 ***
 0.418 ***
 38 [3564.305 ***
 1087.694 ***
 161.3957 ***
 40.000 ***
 39 [3526.335 ***
 1100.277 ***
 P 2
 1 **

1 ***
 6 [3649.627 ***
 1000.000 ***
 180.0000 ***
 71.3957 ***
 39 [3526.335 ***
 1100.277 ***
 156.522 ***
 105.639 ***
 40 [3493.105 ***
 1000.000 ***


P 1	1	***
40	[3493.105	***
	[1000.000	***
	2	***
	4	***
	0.0000	***
	148.500	***
41	[3641.605	***
	[1000.000	***
	3	***
	5	***
9	[3607.688	***
	[3616.959	***
41-9	[90.4433	***
	[2617.179	***
P 2	1	***
41	[3641.605	***
	[1000.000	***
	90.4433	***
	251.3957	***
40	[3493.105	***
	[1000.000	***
	431.296	***
	454.322	***
42	[3636.016	***
	[1431.260	***



To force 41-42 to = 432.96'; 1-41 = 359°44'39" 2639.135';
 41-9 = 90°41'10" 2625.085';
 and 41 would be 7.937' W of 1-6, which is unreasonable.

There is a satisfactory agreement between Trotter and myself over the 41-42 distance. I was unable to find a stone at 41 during a good search. Will set an I.P.

P 1	1	***
5	[3592.986	***
	[1000.128	***
	2	***
	5	***
41	[3641.605	***
	[1000.000	***
5-41	[350.3033	***
	[49.294	***



AZIMUTHS

P 6

25	7	244.39080	***
	R.O.	244.5208	***
	18	265.4908	***
	19	274.3723	***
	20	285.0924	***
	21	331.0451	***
	22	354.0818	***
	23	2.0812	***
	3	1.5924	***
	24	49.1738	***

DAISY WARMOTH ESTATE
***** JOB # 84
COORDINATE FILE 1342WA
LENGTH = 500 POINTS
TIME ON FILE: 0 00 00

***** COGO *****

ENTER & ASSIGN

1	1,000.000	1,000.000
2	2,324.385	1,000.139
3	2,306.919	2,238.887
4	3,604.978	2,239.257
5	3,592.986	1,008.128
6	3,649.627	1,000.000
7	1,495.714	994.381
11	1,433.576	3,603.183
33	3,564.702	1,087.563
34	3,741.549	1,622.775
35	3,560.969	983.571
36	3,605.559	1,021.245
9	3,607.688	3,616.959
10	964.931	3,602.508
37	2,286.310	3,609.733
38	3,564.305	1,087.694
39	3,526.335	1,100.277
40	3,493.105	1,000.000
41	3,641.605	1,000.000
42	3,636.016	1,431.260

START

1,000.000 1,000.000

LOT SUMMARY *Whole S² SE⁴*

1	1,000.000	1,000.000
NE 0 00 00		
1320.802		
31	2,320.802	1,000.000
SE 89 14 34		
2609.961		
37	2,286.310	3,609.733

SW 0 18 48
1321.399
10 964.930 3,602.507

NW 89 13 41
2602.744

1 999.996 999.999

1 1,000.000 1,000.000

NE 14 25 07

0.004 CLOSING LINE
7,854.906 DIST TRAV

1,951,031.059 PRECISION

AREA 3443051 SF 79.0416 ACRES

START

7 1,495.714 994.381

S.S. NE 54 01 14
799.298

17 1,965.298 1,641.195

S.S. NE 61 29 01
670.015

16 1,815.586 1,583.110

TRAV NE 56 39 48
577.710

15 1,813.199 1,477.032

START

7 1,495.714 994.381

TRAV SE 70 50 53
1559.145

26 984.198 2,467.230

START

1 1,000.000 1,000.000

S.S. NE 20 39 53
964.092

12 1,902.064 1,340.227

S.S. NE 19 41 36
1007.250

13 1,948.336 1,339.429

TRAV NE 26 08 34
1056.700

14 1,948.598 1,465.592

START

START

7 1,495.714 994.381

TRAV NE 64 39 08
1368.331

25 2,081.512 2,230.977

S.S. SW 85 49 08
368.673

18 2,054.633 1,863.285

S.S. NW 85 22 37
368.265
19 2,111.195 1,863.910

S.S. NW 74 50 36
126.301
20 2,114.535 2,109.070

S.S. NW 28 55 09
137.685
21 2,202.028 2,164.396

S.S. NW 5 51 42
155.022
22 2,235.724 2,215.145

S.S. NE 2 08 12
225.373
23 2,306.729 2,239.380

S.S. NE 1 59 24
225.394
3 2,306.770 2,238.804

TRAV NE 49 17 38
313.575
24 2,286.020 2,468.687

INV SW 0 03 51
1301.822
26 984.198 2,467.230

B-B SW 0 03 51
3.967
43 980.231 2,467.226

B-B NW 89 13 41
1467.359
1 1,000.000 1,000.000

START 31 2,320.802 1,000.000

START 31 2,320.802 1,000.000

S.S. SE 89 14 34
2609.961
37 2,286.310 3,609.733

B-B SE 89 14 34
1468.833
44 2,301.390 2,468.705

B-B SW 0 03 51
15.371
24 2,286.020 2,468.687

LOT SUMMARY *To E. fence of property*
1 1,000.000 1,000.000

NE 0 00 00
1320.802
31 2,320.802 1,000.000

(6)

SE 89 14 34
1468.833
44 2,301.390 2,468.705

SW 0 03 51
1321.160
43 980.231 2,467.225

NW 89 13 41
1467.359
1 1,000.000 999.999

1 1,000.000 1,000.000

SE 62 47 31

0.001 CLOSING LINE
5,578.154 DIST TRAV

7,188,216.499 PRECISION

AREA 1939167 SF 44.5172 ACRES

LOT SUMMARY *E of fence:*
10 964.931 3,602.508

NW 89 13 40
1135.385
43 980.233 2,467.226

NE 0 03 51
1321.160
44 2,301.392 2,468.706

SE 89 14 34
1141.128
37 2,286.311 3,609.734

SW 0 18 48
1321.399
10 964.932 3,602.508

10 964.931 3,602.508

SE 10 47 18

0.001 CLOSING LINE
4,919.072 DIST TRAV

3,865,766.805 PRECISION

AREA 1503876 SF 34.5242 ACRES

PREDETERMINED AREA-SLIDE
1 1,000.000 1,000.000

NE 0 00 00
1320.802
31 2,320.802 1,000.000

SE 89 14 34
1484.014
45 2,301.190 2,483.884

SW 0 00 00
1321.183
46 980.006 2,483.884

NW	89 13 41	
	1484.019	
1	1,000.000	1,000.000

AREA	1960200 SF	45.0000 ACRES

PREDETERMINED AREA-SLIDE		
1	1,000.000	1,000.000

NE	0 00 00	
	1320.802	
31	2,320.802	1,000.000

SE	89 14 34	
	1466.237	
45	2,301.425	2,466.109

SW	0 00 00	
	1321.179	
46+45	980.246	2,466.109

NW	89 13 41	
	1466.242	
1	1,000.000	1,000.000

AREA	1936716 SF	44.4609 ACRES

Wormoth deed calls for 45 acres, but deed for land remaining in the 1/2 1/4 calls for 35 acres, totaling 80 ac. But the 1/2 1/4 contains only 79.0416 ac. The 45 ac. + 35 ac. were sold off the 80 on the same day (Aug. 9, 1873 - D.R. 41/574+575) so there are no senior rights. Present deed for 35 ac. also calls for 70 rods; however, that distance was added to the description long after 1873. The most equitable way of distributing the shortage is by these proportions:

$$\frac{45}{80} \times 79.0416 = 44.4609$$

$$\frac{35}{80} \times 79.0416 = 34.5807$$

The dividing line should have a bearing that is proportional

to the respective bearings of the N and E of the 1/2 1/4 sec. Establish point 47 at the midpoint of 45-46, about which point the line will rotate to the proportional bearing 50°10'35"W.

ENTER & ASSIGN		
47	1,640.836	2,466.109

START		
31	2,320.802	1,000.000

B-B	SE 89 14 34	
	1468.271	
45	2,301.398	2,468.143

B-B	SW 0 10 35	
	660.565	
47	1,640.836	2,466.109

B-B	SW 0 10 35	
	660.565	
46	980.273	2,464.075

B-B	NW 89 13 41	
	1464.208	
1	1,000.000	1,000.000

LOT SUMMARY (west 1/2 1/4 sec)		
1	1,000.000	1,000.000

NE	0 00 00	
	1320.802	
31	2,320.802	1,000.000

SE	89 14 34	
	1468.271	
45	2,301.398	2,468.143

SW	0 10 35	
	1321.131	
46	980.273	2,464.076

NW	89 13 41	
	1464.208	
1	1,000.000	1,000.000

1	1,000.000	1,000.000

NW	63 42 56	

0.001 CLOSING LINE		
5,574.412 DIST TRAV		

10,371,129.583 PRECISION		

AREA	1936716 SF	44.4609 ACRES

FINAL

LOT SUMMARY (East 35± acres)

10	964.931	3,602.508
NW 89 13 40	1138.536	
46	980.276	2,464.075
NE 0 10 35	1321.131	
45	2,301.400	2,468.143
SE 89 14 34	1141.690	
37	2,286.312	3,609.733
SW 0 18 48	1321.399	
10	964.933	3,602.507
10	964.931	3,602.508
SE 37 11 37		
0.002 CLOSING LINE		
4,922.756 DIST TRAV		
2,110,488.938 PRECISION		
AREA	1506328 SF	34.5805 ACRES


START		
22	2,235.724	2,215.145
INV NE 18 50 43	75.027	
23	2,306.729	2,239.380
B-B SW 18 50 43	2.427	
48	2,304.432	2,238.596
B-B NW 89 14 34	1238.704	
31	2,320.802	1,000.000
START		
1	1,000.000	1,000.000
TRAV NE 0 00 00	571.000	
27	1,571.000	1,000.000
TRAV SE 90 00 00	140.000	
28	1,571.000	1,140.000
TRAV NE 0 00 00	303.200	
29	1,874.200	1,140.000
TRAV NW 90 00 00	140.000	
30	1,874.200	1,000.000

FINAL

NORTH PARCEL

LOT SUMMARY		
30	1,874.200	1,000.000
SE 90 00 00	140.000	
29	1,874.200	1,140.000
NE 82 04 39	202.156	
12	1,902.064	1,340.227
NW 0 59 17	46.279	
13	1,948.336	1,339.428
NE 89 52 51	126.164	
14	1,948.598	1,465.592
SE 4 49 46	135.882	
15	1,813.199	1,477.032
NE 88 42 39	106.105	
16	1,815.586	1,583.110
NE 21 12 19	160.585	
17	1,965.298	1,641.196
NE 68 05 16	239.384	
18	2,054.633	1,863.286
NE 0 37 59	56.565	
19	2,111.194	1,863.911
NE 89 13 10	245.182	
20	2,114.534	2,109.070
NE 32 18 26	103.519	
21	2,202.028	2,164.396
NE 56 25 03	60.917	
22	2,235.723	2,215.146
NE 18 50 43	72.600	
48	2,304.432	2,238.597
NW 89 14 34	1238.704	
31	2,320.802	1,000.001
SW 0 00 00	446.602	
30	1,874.200	1,000.001

30 1,874.200 1,000.000
 NW 75 49 15
 0.001 CLOSING LINE
 3,380.644 DIST TRAV
 4,069,090.144 PRECISION
 AREA 404940 SF 9.2962 ACRES



LOT SUMMARY

1	1,000.000	1,000.000
	NE 0 00 00	
	571.000	
27	1,571.000	1,000.000
	SE 90 00 00	
	140.000	
28	1,571.000	1,140.000
	NE 0 00 00	
	303.200	
29	1,874.200	1,140.000
	NE 82 04 39	
	202.156	
12	1,902.064	1,340.227
	NW 0 59 17	
	46.279	
13	1,948.336	1,339.428
	NE 89 52 51	
	126.164	
14	1,948.598	1,465.592
	SE 4 49 46	
	135.882	
15	1,813.199	1,477.032
	NE 88 42 39	
	106.105 (use 106.10')	
16	1,815.586	1,583.110
	NE 21 12 19	
	160.585 (use 160.59')	
17	1,965.298	1,641.196
	NE 68 05 16	
	239.384	
18	2,054.633	1,863.286
	NE 0 37 59	
	56.565 (use 56.56')	
19	2,111.194	1,863.911

NE 89 13 10
 245.182
 20 2,114.534 2,109.070
 NE 32 18 26
 103.519
 21 2,202.028 2,164.396
 NE 56 25 03
 60.917
 22 2,235.723 2,215.146
 NE 18 50 43
 72.600
 48 2,304.432 2,238.597
 SE 89 14 34
 229.567
 45 2,301.398 2,468.144
 SW 0 10 35
 1321.131
 46 980.273 2,464.076
 NW 89 13 41
 1464.208
 1 1,000.000 1,000.001
 1 1,000.000 1,000.000
 NW 71 04 15
 0.001 CLOSING LINE
 5,584.444 DIST TRAV
 4,103,089.582 PRECISION
 AREA 1489329 SF 34.1903 ACRES

TIME FOR THIS RUN: 1 38 36
 TOTAL TIME ON FILE: 1 38 36
 COORDINATES STORED

LIST


1	1,000.000	1,000.000
2	2,324.385	1,000.139
3	2,306.770	2,238.804
4	3,604.978	2,239.257
5	3,592.986	1,008.128
6	3,649.627	1,000.000
7	1,495.714	994.381
9	3,607.688	3,616.959
10	964.931	3,602.508
11	1,433.576	3,603.183
12	1,902.064	1,340.227
13	1,948.336	1,339.429
14	1,948.598	1,465.592
15	1,813.199	1,477.032
16	1,815.586	1,583.110
17	1,965.298	1,641.195
18	2,054.633	1,863.285
19	2,111.195	1,863.910

20	2,114.535	2,109.070
21	2,202.028	2,164.396
22	2,235.724	2,215.145
23	2,306.729	2,239.380
24	2,286.020	2,468.687
25	2,081.512	2,230.977
26	984.198	2,467.230
27	1,571.000	1,000.000
28	1,571.000	1,140.000
29	1,874.200	1,140.000
30	1,874.200	1,000.000
31	2,320.802	1,000.000
33	3,564.702	1,087.563
34	3,741.549	1,622.775
35	3,560.969	983.571
36	3,605.559	1,021.245
37	2,286.310	3,609.733
38	3,564.305	1,087.694
39	3,526.335	1,100.277
40	3,493.105	1,000.000
41	3,641.605	1,000.000
42	3,636.016	1,431.260
43	980.231	2,467.226
44	2,301.390	2,468.705
45	2,301.398	2,468.143
46	980.273	2,464.075
47	1,640.836	2,466.109
48	2,304.432	2,238.596

IN COMPLET

IED BOND

2 SATTS



Towell 222/481
 Alexander 159/294-5 163/371

41/574,575

stem N3W37L
" S34 1/2 E 38L

432.96
6.56
809.688
12.268

XCCF = 1318.18
1321.32
20.02

72R

72R
1188'

1242.6
1238.9
3.7
XCCF =
1240.2
1238.9
1.3


1242.6
1231.2
11.4
1240.2
1231.2
9.0

1242.648
18.828

19.886
1312.476

69.828
1.058

18 L.S.
11.88'



STANLEY M. SHARTLE

REGISTERED PROFESSIONAL ENGINEER
REGISTERED LAND SURVEYOR

R. R. 1, BOX 33
STILESVILLE, IND. 46180

PHONE 317-539-6225

DAISY WARMOTH ESTATE -- NORTH PARCEL

A part of the South Half of the Southeast Quarter of Section 13, Township 14 North, Range 2 West, Hendricks County, Indiana, described as follows: Beginning on the west line of said half-quarter section 874.20 feet North (assumed bearing) from a cross on a stone at the southwest corner of said half-quarter section; thence East at right angles to said west line 140.00 feet; thence North 82 degrees 04 minutes 39 seconds East 202.16 feet; thence North 0 degrees 59 minutes 17 seconds West 46.28 feet; thence North 89 degrees 52 minutes 51 seconds East 126.16 feet; thence South 4 degrees 49 minutes 46 seconds East 135.88 feet to a stone; thence North 88 degrees 42 minutes 39 seconds East 106.10 feet to a pipe; thence North 21 degrees 12 minutes 19 seconds East 160.59 feet to a stone; thence North 68 degrees 05 minutes 16 seconds East 239.38 feet to a stone; thence North 0 degrees 37 minutes 59 seconds East 56.56 feet; thence North 89 degrees 13 minutes 10 seconds East 245.18 feet to a stone; thence North 32 degrees 18 minutes 26 seconds East 103.52 feet; thence North 56 degrees 25 minutes 03 seconds East 60.92 feet; thence North 18 degrees 50 minutes 43 seconds East 72.60 feet to the north line of said half-quarter section; thence North 89 degrees 14 minutes 34 seconds West along said

north line 1238.70 feet to an iron pin at the northwest corner of said half-quarter section; thence South along the west line of said half-quarter section 446.60 feet to the point of beginning; containing 9.296 acres, more or less. Subject to all legal highways, rights of way, and easements. The west line of said half-quarter section, as marked by a stone at the south line of said line and by an iron pin at the north end thereof, is an assumed meridian to which all cardinal and other bearings herein are oriented.

Given under my hand and seal this 12th day of May 1984:

Stanley M. Shartle

Stanley M. Shartle, Registered Land
Surveyor No. 3431, State of Indiana



STANLEY M. SHARTLE

REGISTERED PROFESSIONAL ENGINEER
REGISTERED LAND SURVEYOR

R. R. 1, BOX 33
STILESVILLE, IND. 46180

PHONE 317-539-6225

DAISY WARMOTH ESTATE -- SOUTH PARCEL

A part of the South Half of the Southeast Quarter of Section 13, Township 14 North, Range 2 West, Hendricks County, Indiana, described as follows: Beginning at a cross on a stone at the southwest corner of said half-quarter section; thence North (assumed bearing) along the west line of said half-quarter section 571.00 feet; thence East at rights angles to said west line 140.00 feet; thence North parallel with said west line 303.20 feet; thence North 82 degrees 04 minutes 39 seconds East 202.16 feet; thence North 0 degrees 59 minutes 17 seconds West 46.28 feet; thence North 89 degrees 52 minutes 51 seconds East 126.16 feet; thence South 4 degrees 49 minutes 46 seconds East 135.88 feet to a stone; thence North 88 degrees 42 minutes 39 seconds East 106.10 feet to a pipe; thence North 21 degrees 12 minutes 19 seconds East 160.59 feet to a stone; thence North 68 degrees 05 minutes 16 seconds East 239.38 feet to a stone; thence North 0 degrees 37 minutes 59 seconds East 56.56 feet; thence North 89 degrees 13 minutes 10 seconds East 245.18 feet to a stone; thence North 32 degrees 18 minutes 26 seconds East 103.52 feet; thence North 56 degrees 25 minutes 03 seconds East 60.92 feet; thence North 18 degrees 50 minutes 43 seconds East 72.60 feet to the north line of said half-quarter

section; thence South 89 degrees 14 minutes 34 seconds East along said north line 229.57 feet to the northeast corner of the west 45/80ths (by square measure) of said half-quarter section; thence South 0 degrees 10 minutes 35 seconds West along the east line of said 45/80ths a distance of 1321.13 feet to the south line of said half-quarter section (said last bearing being an interpolation between the bearing of the west line of said half-quarter section and the bearing of the east line thereof, in the ratio of 45 to 35); thence North 89 degrees 13 minutes 41 seconds West along said south line 1464.21 feet to the point of beginning; containing 34.190 acres, more or less. Subject to all legal highways, rights of way, and easements. The west line of said half-quarter section, as marked by a stone at the south line of said line and by an iron pin at the north end thereof, is an assumed meridian to which all cardinal and other bearings herein are oriented.

Given under my hand and seal this 12th day of May 1984:



Stanley M. Shartle
Stanley M. Shartle, Registered Land
Surveyor No. 3431, State of Indiana

24

83/53 Lewis Whicker to Nelson Woods 3 Mar 1898 Pt. NW SE 13-14-2W
Beg. at NW cor $\frac{1}{4}$ $\frac{1}{4}$; E 6.56 ch. to E National Rd.; SW with E to $\frac{1}{4}$
 $\frac{1}{4}$ W; N 2.25 ch. to leg. 0.74 ac. John W. Truten, surveyor

83/54 N. Woods to Lewis Whicker 10 Mar. 1898 Pt. SW NE 13 Beg.
 8.536 ch. W of SE cor. $\frac{1}{4}$ $\frac{1}{4}$; W 4.79 ch. to E N'l Rd.; NE in E
to point N of leg.; S 1.66 ch. to leg. 0.4 ac.

83/26 N. Woods to Geo. Woods 10 Mar. 1898 Pt. W² NE⁴ 13 Beg. at NW cor.
 $\frac{1}{2}$ $\frac{1}{4}$; S 5 ch. to stone; E 11.414 ch. to stone; S 35.03 ch. to
 $\frac{1}{2}$ $\frac{1}{4}$; E 8.536 ch. to SE cor. W² $\frac{1}{4}$; N 40.02 ch. to NE
cor $\frac{1}{2}$ $\frac{1}{4}$; W 19.96 ch. to leg. 39.875 ac.

41/574 P. Woods to Harlan 9 Aug. 1873 35 ac. off E end. S² SE⁴
13-15-2W Also com. at NW cor. ad. 35 ac.; W 20R; S 2R;
E 20R; N 2R to leg.

Records of correction for 41/574 above are at 114/361 and 115/186, but
they seem to cover a different tract in 13-15-2W, yet say land
meant to be conveyed was in 13-14-2W.

41/575 P. Woods to Cyrus Maston 9 Aug. 1873 Five five ac. off W
end S² SE⁴ 13-14-2W ~~EXC~~ com. 10R E NE cor. W² SE⁴ 13;
W 20R; S 2R; E 20R; N 2R to leg.

97/169 P. Woods to Cyrus Maston - Corrective deed 7 Apr. 1905
Forty-Five ac. off W end S² SE⁴ 13 ~~etc~~ com 10R E of NE cor.
W² SE⁴ 13; W 20R; S 2R; E 20R N 2R to leg.

150/34 Cooper to Harris, Clyde P. & Anna A. 27 Mar. 1943 35 ac, being
70 rods off E side SE SE 13-14-2W cont 35 ac $\pm$, Also,
S $\frac{1}{2}$ of pt N² SE⁴ 13 Beg. in E $\frac{1}{2}$ $\frac{1}{4}$ 12.54 ch E of SW cor;
N 38R 2'; E to E $\frac{1}{2}$ $\frac{1}{4}$; S to SE cor.; W to leg. 10 ac $\pm$
 629

$\frac{157}{177}$ Bradley Admrs. to Dan Wornath et al. 31 May 1967 45 ac.
Entire W and S² SE¹ 13-14-2W.

$\frac{157}{177}$ Kenworthy to same Q.C. 31 May 1967 same land.

$\frac{198}{426}$ Harold J. Martin et al & Ralph Hornum et al. to Larry Gene Stroud
& Janet Faye Stroud 9 Dec. 1965 Starting at SW cor. SE⁴ of
13-14-2W; N on $\frac{1}{4}$ SE⁴ 571' to P.B.; N on $\frac{1}{4}$ 303.2'; E 140.0';
S = $\frac{1}{4}$ 303.2'; W 140.0' to beg. 0.97 ac.

STANLEY M. SHARTLE
REGISTERED PROFESSIONAL ENGINEER
REGISTERED LAND SURVEYOR

SHEET 1 OF 2

Job Daisy Wernoth Est. Date 5-5-84 Hg. Temp.

At


Point	Direction	ZA	Observed slope distance	Mean	Hor. distance
5	2 0°00'00"	90 08 30	1268.63 .63	.63	1268.626
	1 359 49 08	89 47 40	2593.02 .03	.025	2593.008
	R.O. 359 44 17 WRN insulator on dist. pole			.	
	3 315 53 53	90 47 00	1780.26 .26	.26	1780.094
	4 269 04 52	90 45 34	1231.29 .30	.295	1231.187
11	6 171 28 40		.	.	57.22'
			.	.	
	7 0 00 00	89 26 23	2609.67 .67 .66	.667	2609.542
	8 89 03 26	89 31 15	2801.18 .18	.18	2801.082
	9 88 59 55	89 33 37	2174.22 .22	.22	2174.156
25	10 268 43 05	90 22 54	468.66 .65.	.655	468.645
	R.O. 89 10 44 STOP		.	.	
			.	.	
	7 0 00 00	89 14 45	1368.45 .45	.45	1368.331
	R.O. 0 13 00 SE cor. wood cor. post		.	.	
25	18 21 10 00	89 48 20	368.67 .68	.675	368.673
	19 29 58 15±	90 01 52	368.27 .26	.265	368.265
	20 40 30 16	89 08 04	126.31 .32	.315	126.301
	21 86 25 43	90 29 18	137.69 .69	.69	137.685
	22 109 29 10	91 41 50	155.09 .09	.09	155.022
7	23 117 29 04	92 20 00	225.56 .56	.56	225.373
	3 117 20 16	92 19 29	225.58 .58	.58	225.394
	24 164 38 30	91 07 10	313.63 .64	.635	313.575
			.	.	
	25 0 00 00		.	.	
7	R.O. 295 47 36 STOP		.	.	
	17 349 22 06	91 00 00	799.42 .42	.42	799.298
	16 356 49 53	90 59 16	670.12 .11	.115	670.015
	15 352 00 40	91 03 55	577.81 .81	.81	577.710
	11 114 41 54	89 28 07	495.76 .76	.76	495.739
7	5 295 43 24	90 09 40	2097.31 32	.315	2097.307
	11 26 42 44		.	.	
	26 44 29 59	90 38 02	1559.24 .24	.24	1559.145

SHEET 2 OF 2

At _____

5

1



STANLEY M. SHARTLE

LOCATION OF MONUMENT: SECTION 24, T.14 N., R.2 W.

Found: ☒ Set: ☐ Depth: 6.5 inches to stone

Description: set R.R. spike above stone

Bearings to reference objects are magnetic unless a contrary note is shown.

Stone - NW Cor.
Sec. 19-14-1W

conc. cor. post

N74°W
15.52'

N80°E
17.77'

nail & cap in power pole

cor. of stone

S62°W 104.76'

S33°W 102.45'

S94°W 117.22'

stone and fr. house

cor. of block

gar.

cor. of block

CO. RD. 300 W.



Stanley M. Shartle
Stanley M. Shartle, P.E. & L.S.

Date: March 3, 1981


STANLEY M. SHARTLE

LOCATION OF MONUMENT: SECTION 13, T. 14 N., R. 2 W.

Found: ☒ Set: ☐ Depth: 4 inches

Description: stone


Bearings to reference objects are magnetic unless a contrary mode is shown.





Stanley M. Shurtle
Stanley M. Shurtle, P.E. & L.S.

Date: February 28, 1976

S.M.S. 2/28/76







MAP OF FRANKLIN TOWNSHIP

Scale 2 inches to the Mile

